Bronze/Stainless Steel Body Globe Valve for Cryogenic Service SKB Series

Application


The SKB Series globe valves are designed for the handling of cryogenic liquids through trailer, bulk tanks and piping configurations. Our time tested spring loaded stem packing and superior seat design provide for long life and easy maintenance. Internal components are the same for BB Series. Also available in short stem version.


Features

- Superior Flow: Provides high Cv for rapid and reliable trailer and tank loading and unloading
- Top Entry: This valve can be permanently installed in the line and serviced from the top. Bolted bonnet style provides secure integrity
- Soft Seated: Conical PCTFE seat provides a bubble tight seal.
 Less chance of debris trapped in the seat and longer service life
- Stem Packing: V-Ring spring loaded packing provides extended service life without constant packing adjustment
- Sizes: 1/4"though 2" (20mm through 50mm)
- · Ends: Buttweld and Socket Weld
- Service: Liquefied and vaporized atmospheric gases, LNG for trailers, bulk tanks ISO containers and piping configurations
- Temperature Rating: -325°F to +150°F (-198°C to +65°C)
- · Pressure Rating: (Cold, Non-Shock) 720 psig (50 barg)
- Cleaned for oxygen service per CGA G-4.1

Materials

Body	Stainless Steel ASTM A351
Upper Bonnet	Brass ASTM B16
Lower Bonnet	Bronze ASTM B283
Seat Disk	PCTFE ASTM D1430
Seat Retainer	Brass ASTM B16
Stem	Stainless Steel ASTM A582
Spring	Stainless Steel ASTM A313
Packing	PTFE
Handwheel	Chromate Coated Ductile Iron ASTM A395
Bonnet Gasket	PTFE, 25% Glass Filled
Fasteners	Stainless Steel ASTM A320





Ŕ

Ordering Information

	Size	Size		1	A		В		С		BB		C	
Part Number	Inches	DN	Connection	Inches	mm	Cv (Kv)								
SKB9402BW	1/4"	8	Butt Weld											1.7 (1.47)
SKB9402SW	74	0	Socket Weld	2.68	68			3	76	2	51	9.7	246	1.7 (1.47)
SKB9404BW	1/2"	15	Butt Weld	2.00	00			3	76	2	51	9.7	240	E 0 (4 30)
SKB9404SW	/2	15	Socket Weld	1		14.4	366							5.0 (4.30)
SKB9406BW	3/4"	20	Butt Weld			14.4	300							9.4 (8.10)
SKB9406SW	/4	20	Socket Weld	3.62	92			4	102	2.66	67	9.5	241	9.4 (6.10)
SKB9408BW	1"	25	Butt Weld	3.02	92			+	102	2.00	07	9.5	241	14.0 (12.10)
SKB9408SW] '	25	Socket Weld]										14.0 (12.10)
SKB9412BW	11/2"	40	Butt Weld	4.75	121	116	371	4.75	121	3.44	87	9.3	236	20.2 (24.60)
SKB9412SW] 1/2	40	Socket Weld	4.75	121	14.6	3/1	4./5	121	3.44	0/	9.3	230	28.3 (21.60)
SKB9416BW	2"	50	Butt Weld	E 7E	146	16.21	412	E 25	133	4.06	103	9.9	251	E2 (4E 90)
SKB9416SW] 2	50	Socket Weld	5.75	146	10.21	412	5.25	133	4.06	103	9.9	201	53 (45.80)