

RegO Internal Valves - New Series coming soon!

Application

Stainless steel internal valve series for use with LP-Gas or NH₃ on Bobtails, Transports, Storage Plants, or Nurse tanks. Fits in both full and half couplings as well as in-line applications and can be actuated manually, by remote cable, or by various actuator types (sold separately).

Features & Benefits

- Cam or roller type opening provides decades of dependable, low maintenance service
- Stainless steel bodies increase service life even in the harshest of conditions; does not require painting but can be if desired
- Replacement bonnets available (sold separately)
- Removable bonnet (where applicable) provides capability to replace bonnet as needed without disconnecting piping, thereby minimizing downtime; removed bonnet can be repaired for installing again later
- Internal valves without removable bonnets can still be easily serviced as piping does not have to be disconnected to remove and repack stem
- High flow design prevents pump cavitation and efficiency loss, saving time and money
- Built-in excess flow valve and shear studs meet or exceed industry standards to ensure safety

Materials

Body	Stainless Steel
Stem	Stainless Steel
Seat	Stainless Steel
Seat Disc	Nitrile
Springs	Stainless Steel
Stem Seals	PTFE



Ordering Information

Part Number	Inlet	Outlet	Removable Bonnet
A3209F	1 1/4" M. NPT	1 1/4" Flange	Yes
A3212FD	2" 300# ANSI RF Modified Flange*	2" 300# ANSI RF Flange	
A3212F	2" M. NPT		
A3218FD	3" 300# ANSI RF Modified Flange*	3" 300# ANSI RF Flange	
A3213F	3" M. NPT		
A3218F	3" 300# ANSI RF Single Flange*		No

* Valve supplied with 16 nuts and 8 studs for mounting