Presto-Tap® PTSU-KIT

Application

Presto-tap kit with new 12" stainless hose & gauges for obtaining pressure readings and leak testing at tank pressure, first stage, two pound and low pressure (0-20 OZ) locations.

Features

- New 12" Stainless Steel Flex Hose w/ Gauge Bleeder & Straight Quick Adapters
- 300 lb psi/Ambient Temperature gauge w/ Straight Quick Adapter & Cap
- 30 lb psi gauge w/ Straight Quick Adapter & Cap
- 5 lb gauge w/ Straight Quick Adapter & Cap
- 0-20 OZ (0-35" wc) Gauge w/ Straight Quick Adapter & Cap
- · All gauges equipped with magnet and protective cover
- 12" Tool Bag W/ Outer Pockets & Inner Pockets





PTSU-KIT

Ordering Information

Part Number	Description	
PTSU-KIT	Universal Service Tech Diagnostic & Leak Test Kit for All Stages of the Gas System	

PTSFLEX-KITP

Application

Presto-tap 12" Flexible Stainless Steel Hose Assembly w/ Bleeder & ¼" Quick Connect Adapter for Presto-Tap Gauges.



PTSFLEX-KITP



Ordering Information

Part Number	Description
PTSFLEX-KITP	12" Flexible Stainless Steel Hose Assembly w/ Bleeder & 1/4" Quick Connect Adapter

Presto-Tap 90° Quick Connect Fitting RVQA-90F

Application

This 90° quick connect fitting is designed to be fitted on the end of your Presto-Tap hose assembly with straight connectors. This fitting eliminates the need for 2 separate hose assemblies when connecting to the presto-tap on RegO Multivalve ® assemblies.





RVQA-90F

Ordering Information

Part Number	Inlet Connection	Outlet Connection
RVGA-90F	1⁄4" M. Flare	1⁄4" F. Flare