Presto-Tap® LDS2000/RV Fitting

Application

The patented, UL Listed Presto-Tap® LDS2000/RV is designed to obtain pressure readings and perform leak test without breaking into the system by utilizing the proper Presto-Tap® gauge for the selected testing location. Legal installed at any point in the system.

Features

- Brass 1/8" MNPT X 1/4" Flare Housing with #54 Orifice and Everseal
- Valve Core with Viton Seat
- UV Resistant Cap with Nitrile "O" Ring
- UL Label

Materials

Valve Body	Brass
	Stainless Steel w/Nylon Seal & Viton seat
	UV Resistant Plastic w/Nitril "O" Ring
Label	UV resistant Plastic w/Marking





LDS2000RV

Ordering Information - Tank Pressure Application (UL Listed)

Part Number	Thread	Core	Body Wrench Flat	Cap Material	#54 Orifice	Application
LDS2000RV	1/8" M. NPT	Viton	7/16"	UV Resistant Plastic	YES	Tank Pressure

Presto-Tap® RVL & PT-AF14 Fitting

Application

The RVL & PT-AF14 is designed to obtain pressure readings and perform leak test without breaking into the system by utilizing the proper Presto-Tap® gauge installed at the regulator gauge port location.





Ordering Information - Low Pressure Application (Non UL Listed)

Part Number	Thread	Core	Body Wrench Flat	Cap Material	#54 Orifice	Application
RVL	1/8" M. NPT	Viton	7/16"	Brass	NO	Regulator
PT-AF14	1/4" M. NPT	VILOIT	7/10			Installation

Patented Tank Pressure Fitting TPF Series

Application

Low cost, permanently installed fitting between tank service valve and first stage regulator providing leak test capability without the use of tools. Eliminates the need to discard pigtail to access tank pressure.

Features

Easily installed with an adapter such as male POL x 1/4" F. NPT and 1/4" female POL x 1/4" M.NPT





TPF

Ordering Information

Tank Pressure Fitting						
Part Number	Inlet	Outlet	Reduces Emissions			
TPF	1/4" F. NPT	1/4" M. NPT	Up to 90%			