

# Threaded Internal Valves For Bobtail Delivery Trucks, Transports and Stationary Storage Tanks A3213D475

## Application

Designed primarily for use with LP-Gas and anhydrous ammonia for liquid withdrawal; vapor transfer or vapor equalization of bobtail delivery trucks, transports, stationary storage tanks, and in-line installations. The valve may be operated manually by cable or pneumatically.



COMING SOON



A3213D475

## Ordering Information

Part Number	Inlet Connection	Outlet Connection	LPG Closing Flow		Accessories			
			Half	Full	Pneumatic Actuator	Rotary Actuator	Electric Actuator	Thermal Latch
A3213D475	3" M. NPT	3" F. NPT	475	385	A3213PA	A3213RA A3213OA	A3213EA	A3213TL

## First Stage Regulator LV4403TR66

### Application

Provides accurate first stage regulation in two-stage bulk tank systems. Reduce tank pressure to an intermediate pressure of 5 to 10 PSIG (0.34 to 0.69 BARG). Also used to supply high pressure burners for applications like industrial furnaces or boilers. Also incorporated in multiple cylinder installations.



LV4403TR66

## Ordering Information

Part Number	Inlet Connection	Outlet Connection	Orifice Size	Factory Delivery Pressure	Adjustment Range	Bonnet Vent Position	Vapor Capacity BTU/hr Propane*
LV4403TR66	3/4" F. NPT	3/4" F. NPT	1/4" (6.25mm)	10 PSIG @ 50 PSIG Inlet (0.69 Bar @ 3.44 Bar inlet)	5-10 PSIG (0.34 - 0.69 Bar)	Over Outlet	2,500,000 BTU/hr (53 KG/hr)

## LPV-Series Ball Valve with Presto-Tap® fitting

### Application

Gas ball valve fitted with LDS2000RV Presto-Tap® fitting in the outlet tap. Eliminates need for test tee and labor for installation. Provides quick access to obtain pressure readings and perform leak tests without breaking into the system by utilizing the proper Presto-Tap® gauge for the selected testing location.



LPV-6

LPV-4

## Ordering Information

Part Number	Inlet	Outlet	Reduces Emissions
LPV-4	1/2" F. NPT	1/2" M. NPT	Up to 90%
LPV-6	3/4" F. NPT	3/4" M. NPT	